

# **> > VIKING™ V1 MULTIPLE-POSITION EARMUFF**

# **PRODUCT INFORMATION**

The Viking multiple-position earmuff series gives workers flexibility to wear their earmuffs over-the-head, behind-the-head or under-the-chin. Viking earmuffs can be worn with other PPE including visors, face shields, respirators and welding shields. A headband strap provides additional security, keeping earcups in place when worn other than above the head.

#### **PRODUCT FEATURES**

- ⇒ Air Flow Control™ Technology provides better, consistent attenuation, especially at low frequencies.
- ⇒ Optimal protection for virtually all noise frequency environments.
- ⇒ Non-Deforming 3-position headband allows wearer to select position – Over-the-Head, Behind-the-Head or Under-the-Chin.
- ⇒ Wear with other PPE including helmets, respirators and welding shields.
- ⇒ Inner-Ventilated headband provides better comfort and minimized pressure on head.
- ⇒ Soft, comfortable contact surface.
- ⇒ Headband breathes easier in warm/humid climates
- ⇒ Alternative to cap-mounted earmuffs.
- ⇒ Robust construction withstands rough treatment in the toughest environments.
- ⇒ Headband strap improves comfort, attenuation and fit when worn BTH or UTC.
- ⇒ Snap in ear cushions makes cushion replacement quick and easy.
- $\Rightarrow$  Dielectric construction does not conduct electricity.
- ⇒ Suitable for almost all workplaces, especially
- ⇒ electrical and mining environments.
- ⇒ Low profile earcup design.

## **APPLICATIONS**

⇒ Noise environments between 105dB to less than 110dB(A).



#### **TECHNICAL INFORMATION**

Materials: Headband - Outer - Acetal

- Inner - Low density polyethylene

Cup - ABS

Ear Cushion - PVC/PUR-E (Polyurethane)

Hygiene Kit: Part # 1011998

Headband force: 8.9N Weight: 191grams

#### **STANDARDS**

⇒ Approved to AS/NZS 1270:2002 License number 1133

⇒ SLC<sub>80</sub> 28dB Class 5 (in OTH position)

Frequency	125	250	500	1000	2000	4000	8000
Mean Value dB	19.3	22.6	26.8	30.6	32.6	37.6	36.0
Std Deviation dB	4.2	3.8	4.4	3.6	3.5	3.3	4.2
Mean-Std Dev dB	15.1	18.8	22.4	27.0	29.1	34.3	31.8

## ORDERING INFORMATION

Part Number	Description	Pairs Per Box	Min order (box)		Case Dimensions L x W x H (mm)	Case Weight	Bar code
1010925	Viking V1- 3 position	1	20	235g	440 x 410 x 400	5.30kg	033552011316

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF PERSONAL PROTECTIVE PRODUCTS AVAILABLE FROM SPERIAN PROTECTION AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. SPERIAN PROTECTION RECOMMENDS ALL USERS OF ANY PERSONAL PROTECTIVE EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY.

Sperian Protection Australia Pty Ltd Ph Aust: 1300 139 166 NZ: 0800 322 200 www.sperianprotection.com.au