

# HyFlex® 11-630 11-638

MECHANICAL PROTECTION

 CUT PROTECTION

**M** MEDIUM

STYLE #	CONSTRUCTION	GAUGE	LINER MATERIAL	COATING MATERIAL	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-630	Knitted	13	Nylon Lycra® HPPE Cotton Kevlar®	Polyurethane	Palm coated	Knitwrist	Grey	6, 7, 8, 9, 10, 11	215 - 275	12 pairs in a bag, 12 bags in a carton
11-638	Knitted	13	Nylon Lycra® HPPE Cotton Kevlar®	Polyurethane	Palm coated	Long knitwrist	Grey	6, 7, 8, 9, 10, 11	290 - 340	12 pairs in a bag, 12 bags in a carton



## Dexterity with superb cut resistance for optimal productivity

### PRIMARY INDUSTRIES



### IDEAL APPLICATIONS

- Glass manufacturing
- Aeronautics
- Assembly of white goods
- Plastics injection and moulding
- Assembling metal parts and components
- Handling sharp or irregular-edged metal parts

### DESCRIPTION

- The liners of the HyFlex® 11-630 and 11-638 gloves have a yarn structure that contains an optimal rate of HPPE. This offers high levels of cut resistance, for a safe use in controlling, handling and assembly applications involving contacts with sharp pieces.
- The Lycra® in the liners of both gloves, as well as the polyurethane coating, provides excellent flexibility and fit.
- The specific formulation of the polyurethane dipping provides a secure grip on dry or slightly oily pieces.
- The PU formulation also increases abrasion resistance on the gloves' work surface.



EN 388:2003  
4443

**CATEGORY II**

Print date: 30-11-2017

### Ansell Healthcare Europe N.V. (European Head Office)

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

<http://www.ansell.eu> • E-mail [info@ansell.eu](mailto:info@ansell.eu)