



North Safety Products

Product Data Sheet – RESPIRATORY PROTECTION – Class 2 Filters

Product RPF1 N65754201



Description	EPDM Direct Thread Full Face Mask									
Physical Properties	<ul style="list-style-type: none"> •Face piece made from soft, hypoallergenic elastomer. •Contoured sealing flange, cradle suspension system and Headband yoke. •Exceptionally low breathing resistance. •Positive pressure fit check without removing cover, eliminates the risk of improper seal and reduced protection due to lost or worn sealing gaskets. •Minimizes replacement parts, ease of maintenance and no cartridge receptacles to clean. 									
Standards	EN 136 (Class 2). Filter connector to EN 148-1 (40mm DIN thread). Visor: EN 166B									
Uses	•Can be used with EN40 mm thread connection, powered filter device in combination with Airbelt or Compact Air. Also available as continues flow compressed airline apparatus, using North CF2000 Plus.									
Protection against: (see cartridges & index filter type)	<table border="1"> <tr> <td>P</td> <td>A</td> <td>AX</td> <td>B</td> <td>E</td> <td>K</td> <td>HG</td> <td>CO</td> <td>P3</td> </tr> </table>	P	A	AX	B	E	K	HG	CO	P3
P	A	AX	B	E	K	HG	CO	P3		
Precautions	<ul style="list-style-type: none"> •Not to be used in areas that are Oxygen deficient i.e. where Oxygen is below 19%. •Not to be used where the contaminant is IDLH. •Only to be used with North Safety Products approved class 2 series screw in cartridges. •Only to be used with the applicable cartridges to protect from the particular hazard. •Not to be worn with facial hair, i.e. no beards or moustaches. 									