3AA ProPolymer® HAZ-LO® Safety Approved Flashlight



Material/Lens Impact and chemical resistant Engineering Polymer resin; o-ring sealed and vented. Available in high visibility yellow, orange or black. Unbreakable polycarbonate lens with scratch resistant coating

Dims/Weight Length: 7.00 in. (17.78 cm); Body thickness: 1.05 in. (2.67 cm); Width: 1.50 in. (3.81 cm); Face cap diameter: 1.93 in. (4.90 cm) 7.5 oz (213 grams) with batteries (included with purchase)

Light Source C4® LED technology, shock-proof with a 50,000 hour lifetime. Smooth parabolic reflector produces a tight beam with optimum peripheral illumination. Regulated run time provides consistent performance throughout battery life

Switch Push-button tail switch. Sealed switch design protects it from corrosion caused by battery leakage

Battery • 3 "AA" alkaline batteries reduce battery and recycling costs by 25%

Combination of visual and mechanical polarity protection ensures correct installation of batteries

· Light designed to not power on if batteries are installed incorrectly

Features • High-performance, anti-static, thermoplastic material resistant to chemicals and solvents

• "Captured locking" set screw will not back out - prevents FOD (Foreign Object Debris)

· Safety measure: Set screw helps to avoid batteries being changed out, or the housing inadvertently being opened in a hazardous environment

· Set screw goes into a metal tray that evenly distributes pressure to protect the body from over-tightening of the set screw

• One body electronic LED module mechanically attached to electronic assembly

• IP64/IPX7 rated; dust-tight, waterproof to 1m for 30 minute

• 3 meter impact resistance tested

• Ergonomically designed for maximum hand comfort

Approvals C-UL-US Classified Class I, Division 1, Groups A, B, C, D; Class II, Division 1, Groups E, F, G; Class III; Exia; T-Class: T4

Most models meet applicable European Community Directives

MSHA MSHA Permissible Flashlight. Approval No. 20-A140003-0 Tested for Intrinsic Safety in Methane-Air mixtures only.

ATEX ATEX-approved for Category 1 (Zone 0) locations

IDEMKO 13 ATEX 1214468X; II 1G Ex ia IIC T4 Ga; II 1D Ex ia IIIC To118°C Da

IECEx UL 14.0032X; Ex ia IIC T4 Ga; Ex ia IIIC To118°C Da

InMetro UL-BR 14.0185X; Ex ia IIC T4 Ga; Ex ia IIIC To118°C Da

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Part #
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Yellow	080926-68720-2	68720
3AA ProPolymer HAZ-LO with alkaline batteries - Box - Yellow	080926-68723-3	68723
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Black	080926-68721-9	68721
3AA ProPolymer HAZ-LO with alkaline batteries - Box - Black	080926-68724-0	68724
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Orange	080926-68722-6	68722
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Yellow (InMetro)	080926-68726-4	68726
3AA ProPolymer HAZ-LO with alkaline batteries - Blister - Orange (InMetro)	080926-68727-1	68727





Item	UPC	Part #
4AA/3AA helmet mount	080926-68085-2	68085
4AA/3AA Gallet mount	080926-68086-9	68086
Nylon Holster	080926-68905-3	68905
Poly Mount Kit	080926-68089-0	68089
Rubber Helmet Strap	080926-99075-3	99075
3AA/4AA ProPolymer Series Belt Clip	080926-68088-3	68088
Lanyard with Push Button Slide (not shown)	080926-72024-4	72024

