



- Material/ Lens** Housing and facecap made from high impact, anti static, non-conductive super tough nylon construction with rubberized cushioned-grip handle. One way valve for case venting. Available in international safety orange. Unbreakable polycarbonate lens with scratch-resistant coating
- Dims/Weight** Length: 7.78 in. (19.76 cm); Width: 5 in. (12.7 cm); Height: 6.50 in. (16.51 cm); 1.93 lbs (875 grams) with battery
- Light Source** C4® LED with high, low and blink modes:
 - High for a bright, far-reaching beam: 180 lumens; 100,000 candela; 632m beam; runs 3.5 hours
 - Low for a less intense beam and longer run time: 70 lumens; 40,000 candela; 400m beam; runs 7.5 hours
 - Blink for signaling: runs 5.5 hours
- Deep-dish parabolic reflector produces a tight beam with optimum peripheral illumination to aid in navigation
 Optimized electronics provide regulated intensity
- Switch** Dual-direction toggle switch is easy to use with gloved hands
- Battery** Lithium ion battery recharges in 5 hours
- Features** - Operating temperature: -20°F to 130°F. (To maintain hazardous locations rating: -20°C to 35°C)
 - IP66; dust tight and water-resistant
 - 2 meter impact resistance tested
 - Serialized for positive identification
- Models:** Standard System - Includes quick-release shoulder strap, AC/DC chargers and rack
Vehicle Mount System - Includes vehicle-mountable hard-wire rack and quick-release shoulder strap
- Approvals** **ATEX:** II 3G Ex ic nA IIC T5 Gc II 3D Ex tc IIIC T54°C Dc FTZU 08 ATEX 0139X
IECEx: Ex ic nA IIC T5 Gc Ex tc IIIC T54°C Dc IECEx FTZU 15.0038X
InMetro Ex n A ic IIC T5 Gc Ex tc IIIC T54° C Dc IP66 DNV 16.0076X
 Rack meets requirements of NFPA 1901-14.1.11.2 (2003) mounted in any position
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.

Item	UPC	Item #
Vulcan LED ATEX Standard System with quick release shoulder strap. IEC Type C (230V) AC/12V DC - Orange	080926-44753-0	44753
Vulcan LED Standard System with quick release shoulder strap. IEC Type C (230V) AC/12V DC - Orange InMetro	080926-44755-5	44755
Vulcan LED ATEX Standard System with quick release shoulder strap. IEC Type G (240V) AC/12V DC - Orange	080926-44752-3	44752
Vulcan LED ATEX Standard System with quick release shoulder strap. IEC Type A (100V/120V) AC/12V DC - Orange	080926-44754-7	44754
Vulcan LED ATEX Vehicle Mount System with quick release shoulder strap. 12V DC direct wire rack - Orange	080926-44751-6	44751
Vulcan LED Vehicle Mount System with quick release shoulder strap. 12V DC direct wire rack - Orange InMetro	080926-44755-4	44755
Vulcan LED ATEX Light Only- with quick release shoulder strap - Orange	080926-44750-9	44750
Vulcan LED Light Only- with quick release shoulder strap - Orange InMetro	080926-44756-1	44756



22060



22061



22062



#22051



#44610



#44102 Standard System Charge Rack
#44132 Direct Wire DC Charge Rack



#44050

Item		UPC	Part #
DC2 direct wire charge cord		080926-22050-8	22050
DC1 Charge Cord		080926-22051-5	22051
IEC Type C (230V) AC charge cord		080926-22061-4	22061
IEC Type A (100V/120V) AC charge cord		080926-22060-7	22060
IEC Type G (240V) AC charge cord		080926-22062-1	22062
Battery - Li-ion		080926-44610-6	44610
Standard System Mounting Rack	Black	080926-44102-6	44102
Direct Wire 12V DC Mounting Rack	Black	080926-44132-3	44132
Quick Release Strap		080926-44050-0	44050



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600 Phone • 610-631-0712 Fax
www.streamlight.com Vulcan LED ATEX & InMetro 2/17