



PRODUCT NUMBER: 2058685

## CRYOGENIC

Protection against small drops of liquid gas up to -170°C.

### Overview

**Reference Number**

2058685

**Product Type**

Gloves

**Range**

Specific Protection

**Brand**

Honeywell

**Brand formerly known as**

SPERIAN

**Industry**

- Chemical Industries
- Petro-chemical

**Product Use**

Protection against small drops of liquid gas up to -170°C.

### Features & Benefits

**Feature**

Water-repellent silicone cowhide grain leather glove

Fully lined with 2 aluminium/fleece layers

Gunn cut, winged thumb, crispin type

Reinforcement between thumb and index

200 mm split leather cuff

Velcro® adjustment strap on side of the palm

**Benefit**

**COMFORT**

The US assembly, the winged thumb and flexibility of the materials used make this glove anatomical, thus providing excellent comfort.

The Velcro fastening tab gives the glove good support.

**RESISTANCE**

## CRYOGENIC - 2058685

The silicone cowhide grain leather ensures good flexibility, even at a low temperature as well as water repellence and good mechanical protection.

Its polar double insulation offers outstanding protection against the cold and rays.

The reinforcement between the thumb and index finger increases the glove's mechanical resistance and durability by strengthening the areas of wear.

### HYGIENE

The hide cuff offers good forearm protection against mechanical hazards and limits any risk of intrusion.

## Technical Description

### Description

CE CATEGORY : II Intermediary risks

In accordance with standards :

EN 420-2003 EEC Basic standards

EN 388-2003 Mechanical Hazards

EN 511-2006 Cold protection

### CHARACTERISTICS :

Water-repellent silicone cowhide grain leather glove

Fully lined with 2 aluminium/fleece layers

Gunn cut, winged thumb, crispin type

Reinforcement between thumb and index

20 cm split leather cuff

Velcro® adjustment strap on side of the palm

### Product Technology

Cut and Sewn

### Coating Type

Leather

### Thickness

1.1/1.3 mm

### Harmlessness

In conformity with the European standards

### Dexterity

Class 5

### Sizes

9 to 11

## EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance (Coupe test)	2
Tear resistance	2
Puncture resistance	2

## EN 511- Protection in cold temperatures:

Resistance to conductive cold	2
Resistance to contact cold	2
Water permeability	0

## Packaging Label

### Tagging

CE HONEYWELL

2058685 XX

EN 420

EN 388 : 3222

EN 511 : 220

## Certifications

### EC Category PPE

2

### EC Certificate Number

0075/797/162/01/09/0001

### EC Attestation

 EC Attestation

**EC Attestation Number**

0075/797/162/01/09/0001

## Additional Information

**User Manual**

UI 105

**User Information Sheet**

105

## Maintenance

**Storage Information**

Minimum packaging 1 pair.

Cartons of 25 pairs.

**Care Instructions**

In order to keep its properties, this article should not be cleaned.