



Colours: black yellow Ref: BF BJ



Polymer toe cap* Composite anti-perforation mid-sole*

Outside height (size 8): 370 mm Weight (size 8): 1900g / pair

Elastomer: fireproofed NBR / CR (fireproofed nitrile/polychloroprene rubber)

Reference: FIREMAN SA Boots (safety toe cap + anti-perforation mid-sole)

Antistatic

Low temperature resistance

Slip resistance

Mechanical resistance

Excellent resistance to heat flow, heat contact, fire. Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents. Excellent resistance to abrasion and cuts Used with chemical protective suits (satisfy permeation tests according to EN 943-2).

Comply with standards :

Chemical resistance

Thermal resistance

EN 15090 type 3 HI3 Boots for emergency situation and fire with toxic chemicals emission.

EN ISO 20345 S5 HRO SRC Heel shock absorption. Antistatic. Resistance to heat contact (HRO).

EN 13832-3 J P Q Boots highly resistant to chemicals : N-Heptane (J) Hydrogen peroxide (P) Isopropanol (Q)

EN 13287 Sole slip resistance (SRC) : - Steel floor. - Ceramic floor.

Marine fire protection equipment certified by SEE-BG, notified body $N^\circ0736$.

* Sizes 3 and 4.5 have steel toe cap and steel midsole.

Sizes:

 FR
 36
 37/38
 39
 40/41
 42
 43
 44
 45
 46/47
 48
 49/50

 UK
 3
 4.5
 5.5
 7
 8
 9
 9.5
 10.5
 11.5
 13
 14

Options:





ETCHÉ SÉCURITÉ: ZA Ordokia - 64130 VIODOS ABENSE de BAS – FRANCE Tel : 33 (0)5 59 28 05 41 - fax : 33 (0)5 59 28 30 10 - www.etchesecurite.com