

**NEW!**

## Fall arresters

retractable type

# UltrOn

retractable type fall arrester with rescue lifting device

EN 360, EN 1496 class B



Ref.: UltrOn - cable length 15 m.

Cable material: galvanized steel  
Maximum cable length: 15 m  
Case material: aluminium alloy  
Max working load: 140 kg  
Weight: approx 11 kg  
Dimensions: 300 x 230 x 175 mm  
Static strength: not less than 14 kN  
Braking force: less than 6 kN  
Fall arresting height: less than 2 m

UltrOn is a combination of a retractable type fall arrester and a rescue lifting device. The device is equipped with a manual winch featuring lift and descent functions. In order to install on the tripod, first mount an adequate mounting clamp;

- Connector has a fall indicator; the design requires no energy absorber;
- Permissible work load: 140 kg;
- With the ratio used in the mechanism it is possible to make one turn of the drum per 7.4 turns of the winch's crank;
- Retractable type fall arrester UltrOn is a component of personal fall protection equipment and conforms to EN 360 and EN 1496/B.



eye for anchoring

handle for transportation warning: **do not use for anchoring!**

5 mm galvanized steel cable

AZ 002 ASI with indicator aluminium, galvanized steel opening: 24 mm weight: 220 g



### SWIVEL SNAP HOOKS

PRICE INCLUDES ALL VERSIONS OF SWIVEL SNAP HOOKS



AZ 030 aluminium, galvanized steel opening: 23 mm weight: 200 g



AZ 031T aluminium, galvanized steel opening: 23 mm weight: 200 g twist lock



AZ 050 galvanized steel opening: 23 mm weight: 360 g



AZ 051T galvanized steel opening: 23 mm weight: 360 g



AZ 002AS aluminium, galvanized steel opening: 24 mm weight: 215 g



AZ 060 galvanized steel opening: 21 mm weight: 380 g

### SWIVEL SNAP HOOKS WITH FALL INDICATOR



AZ 030I with indicator aluminium, galvanized steel opening: 23 mm weight: 200 g



AZ 031TI with indicator aluminium, galvanized steel opening: 23 mm weight: 200 g



AZ 060I with indicator galvanized steel opening: 21 mm weight: 380 g