



fire brigade / disaster control

indu

construction sites

agriculture

potable water

special products

accessories

SYNTHETIC DRAGON

Fire hose MADE FOR HELL

Flame resistant heavy duty lay flat hose for all fire-fighting operations. Circular woven jacket out of 100% high tenacity synthetic yarn, embedded in a special flame retardant high grade Nitrile/PVC compound using the "Through-the-weave-extrusion process". Offers high resistance to acids, salt solutions, oil, fuel and many more chemicals.

ADVANTAGES

- · Lightweight lay flat hose
- · Minimum friction loss
- · High aging resistance
- · Ribs on outside lining for high abrasion resistance
- · High resistance to oil, chemicals and fuel
- · Excellent resistance to ozone and weathering
- · Cold-resistant up to -35°C
- Heat-resistant up to +100°C
- · Easy maintenance and handling



SERVICE

- · Standard colour orange, other colours on request
- · Light ribless version available
- · Individual marking available
- · Binding with international couplings available on request
- · Other diameters on request
- · Available in lengths up to 200 m

| Flame resistance test acc. DIN 14811, destructive test. | | | | | |
|---|-------------|-----------|--|--|--|
| Hose Type | Temperature | Endurance | | | |
| Type 1 | 940°C | 11 sec | | | |
| Type 2 | 940°C | 12 sec | | | |
| Type 3 | 940°C | 39 sec | | | |
| Dragon | 940°C | > 1 h | | | |

| Diameter Inch (mm) | Weight g/m | Burst pressure (PSI) | Working pressure (PSI) | Test pressure (PSI) |
|--------------------|------------|----------------------|------------------------|---------------------|
| 1" (25) | 180 | 725 | 300 | 600 |
| 1 ¼" (32) | 230 | 725 | 300 | 600 |
| 1 ½" (38) | 310 | 725 | 300 | 600 |
| 1 ¾" (45) | 346 | 725 | 300 | 600 |
| 2" (52) | 420 | 725 | 300 | 600 |
| 2 ½" (65) | 530 | 725 | 300 | 600 |
| 2 ¾" (70) | 590 | 725 | 300 | 600 |
| 3" (75) | 650 | 725 | 300 | 600 |
| 3 ½" (90) | 810 | 580 | 200 | 450 |
| 4" (102) | 850 | 580 | 200 | 450 |
| 5" (127) | 1350 | 435 | 150 | 350 |
| 6" (152) | 1600 | 435 | 150 | 350 |
| 8" (203) | 3000 | 435 | 150 | 350 |